

## **ALL CONTRACTS**

Solvent, Eco-solvent or UV curable printed vinyl graphics  
UV laminate suitable for vinyl; aids in removal and protects from scratching and fading of graphics  
All applications should include minimum 1/2" corner radius to prevent edge peeling.

PLOTTER CUT VINYL is prohibited unless in the case that it is an accent or flourish placed ON TOP of a full-size printed graphic; NO COMPLEX LAYERING.

## **3 MONTH and 6 MONTH CONTRACTS**

3-4-mil, PVC film featuring a high level of pigmentation for enhanced covering power, as well as specially formulated grey-pigmented adhesive that enables the graphic to be removed without adhesive transfer.

### **Adhesive**

Grey, solvent-based, removable adhesive

### **Applications**

Designed for short to medium-term exterior transit and general signage graphics

## ***RECOMMENDED***

ORAJET® Series 3109 Transit Graphics Inkjet Media, ORAJET® Series 3691 Removable Inkjet media preferred. Other manufacturers' equivalent will be accepted pending approval from OPT.

## **1 YEAR+ CONTRACTS (signs and full wraps)**

2-3-mil, premium cast or ultra-calendered PVC; air-egress technology preferred.

### **Adhesive**

Grey, solvent-based, repositionable, permanent adhesive that can be removed with little or no adhesive residue for up to four years

### **Applications**

Simple to complex curves, rivets and corrugations

## ***RECOMMENDED***

ORAJET® Series 3951RA and Series 3551RA or other manufacturers' equivalent; Other manufacturers' equivalent will be accepted pending approval from OPT.

## **REFLECTIVE**

Applicable for all contract lengths; Printed inkjet specialty reflective media with UV laminate

All REFLECTIVE applications MUST include a base application of the non-reflective media listed above that best accommodates contract length

## **PERFORATED WINDOW FILM**

### **Description**

Perforated, 5.5-mil PVC film available in white with a gloss finish and black backing. 50% printable area.

### **Adhesive**

Clear, solvent-based, permanent adhesive

### **Areas of Use**

For short- and medium-term window graphics applications

## ***RECOMMENDED***

ORAJET 3675 Perforated Window Graphics Inkjet Media (50/50) or other manufacturers' equivalent; Other manufacturers' equivalent will be accepted pending approval from OPT.

All requirements and recommendations are subject to change without notice. OPT has the final say in material usage, applicability, and installation techniques.